

	RD818	RD817	RD816	RD815	RD814	RD813
Model	DM-E 15000	DM-E 13000	DM-E 10000	DM-E 7000	DM-E 5000	DM-E 3000
Rated voltage (V)	220-240V/50Hz, 120V/60Hz					
Power consumption (W)	130	95	75	50	30	22
Power cable length (M)	10	10	10	10	10	10
Max.flow rate (L/H)	15000	13000	9800	7000	5200	3200
Max.head height (M)	5,5	5,0	5,0	4,0	3,0	2,8
Product size LxWxH(mm)	194×110×152	194×110×152	185×98×135	177×98×135	177×98×135	177×98×135
Packagesize LxWxH (mm)	270x200x180	270x200x180	270x195x155	270x195x155	270x195x155	235x135x110
Connection pressure-side	2"	2"	2"	2"	2"	1,0
Connection suction-side	2"	2"	2"	2"	2"	1,0
Connection for hose(mm)	40/32/25/20	40/32/25/20	40/32/25/20	40/32/25/20	40/32/25/20	φ25/20
Electronically adjustable	NO	NO	NO	NO	NO	NO
Setup type	Can be setup underwater & dry					

Specifications:

Adopt the permanent magnet brushless motor, high-efficiency.

Multi-Application: filter, waterfall, or water features etc.

Adjustable water flow.

Work with the electronic flow controller FC-300E, or with smart WiFi controller MFC-300E(Optional).